

What is smart metering?

Meter Smart İS energy an measurement device that measures the real time consumed energy by a customer.

It provides a two way flow of information between consumers and suppliers providing better controllability and efficiency.

Need for smart metering

With shift global to less а predictable renewable energy sources, utilities companies need more precise data to balance loads on the Smart Grid. At the same time, consumers want greater control over their energy usage.

Smart metering system is an advanced, flexible, interoperable, proofing future that system market all connects energy participants such as customers, utilities and regulators.

We have designed and prototyped different types of IoT smart meters, all equipped with an internet connection to communicate with the server-side of our network infrastructure in order to join the smart grid.











A new three-phase Smart Meter for Cloud connection: network 2 architecture and performances

Andrea Altomonte¹, Francesco Arena², Michele Riccio¹ and Andrea Irace¹

¹ Dept. of Electrical Eng. and Information Technologies, University of Naples Federico II, Naples, IT. michele.riccio@unina.it (M. R.); andrea.irace@unina.it (A. I.). ² ARCA Holding LTD, Sloan Place, London, UK. <u>ing.arenafrancesco@gmail.com</u>

- * Correspondence: andr.altomonte@studenti.unina.it
- Presented at 8th International Electronic Conference on Sensors and Applications, 1–15 November 2021; 9 Available online: https://ecsa-8.sciforum.net.

Our technology

Enabling up to Class 0.2 meter accuracy and beyond

Easy to extend the design from single to polyphase meters

Scalability of the smart grid



All the smart meters belonging to the network communicate with the cloud through the IoT MQTT protocol.

On the cloud side, data storage takes place, while the display of smart meter data takes place via a WebApp from a mobile device or PC.



Technology readiness level

Our complete smart metering system, i.e. three smart meter prototypes and the network infrastructure, was tested in an industrially relevant environment.



e SM1	Pow 20	ver active SM2	Power active SM3	Catture finestra	
44 7.4000	000- - - - - - - 1000 - - - - - - - - -	4000- 1.5 5000	• 215.3 500 v		
	Тс	otal active power			
					Active Power SM1 Active Power SM2 Active Power SM3
11:		:00 12: ime	30 13:	.00 13:3	0