



Proceeding Paper

Integrated Water Resource Management Using Water Evaluation and Planning Model: A Case Study of Lower Bari Doab Canal, Pakistan ⁺

Hira Khanam ^{1,*}, Sikandar Ali ^{1,2,*}, Muhammad Zaman ¹, Muhammad Adnan Shahid ^{1,2,*}, Hafsa Muzammil ^{1,2}, Zeeshan Khan ¹, Muhammad Safdar ^{1,2} and Muhammad Danish Majeed ^{1,2}

- ¹ Department of Irrigation & Drainage, University of Agriculture, Faisalabad 38000, Punjab, Pakistan; email1@email.com (M.Z.); email2@email.com (H.M.); email3@email.com (Z.K.); email4@email.com (M.S.); email5@email.com (M.D.M.)
- ² Agricultural Remote Sensing Lab (ARSL), University of Agriculture, Faisalabad 38000, Punjab, Pakistan
- Correspondence: hirakhanam020@gmail.com (H.K.); sikandar_ali@uaf.edu.pk (S.A.); adnan.wmrc@gmail.com (M.A.S.)
- + Presented at the 7th International Electronic Conference on Water Sciences, 15–30 March 2023; Available online: https://ecws-7.sciforum.net.

Abstract: Fresh Water scarcity is a global concern and is caused by the overuse of water, exceeding the sustainable level. In Pakistan, overpopulation, climate change alleviation, and economic development are influencing the asset of water. For water management, development, and conservation; policymakers need to formulate the right plans and projects. For this purpose, they need to evaluate the impact of different projects and plans and require considerable data and information. Different tools are being adopted for Integrated Water Resource Management. Among them, WEAP is userfriendly, reliable, and efficient; and is used widely across the globe. It will aid the policymakers to develop suitable projects and plans. This study was carried out by using WEAP, in the Lower Bari Doab Canal Command area (LBDC), Punjab, Pakistan. This study throws light on the current water allocation situation and simulated scenarios of population growth rates and economic growth to evaluate the future water demand situation. The results of the current account year (2015) showed that the domestic water demand of Okara (101.51 MCM) and the Agricultural water demand (1713 MCM) of Sahiwal were seen to be the maximum among the four districts. Unmet demand was found to be maximum for the districts laying in the tail end (Sahiwal and Khanewal). The results of the scenarios showed that if the current water consumption, population growth, and economic development continue, unmet demand will increase in the future and if the population grows at a higher rate and economic development increases it will result in Higher Unmet water demand in the coming years. WEAP was found to the user a friendly and efficient model to figure out the water demand.

Keywords: demand; WEAP; LBDC; unmet demand

1. Introduction

The sources of water in Pakistan are natural or artificial. Accessibility of water is declining globally due to environmental and climate changes, industrialization, contamination, and other anthropogenic activities. Around 2 billion people are living in areas that are under water stress, and they are not able to use freshwater resources due to the uneven distribution of freshwater (Oki and Kanae, 2006). The water crisis has been on the list of top 5 world crises for the last 6 years and has been placed in fourth position for the year 2019. (Anonymous, 2019). Shortage of water is escalating globally and is causing dangers to the life of whole species of animals and plants.

Citation: Khanam, H.; Ali, S.; Zaman, M.; Shahid, M.A.; Muzammil, H.; Khan, Z.; Safdar, M.; Majeed, M.D. Integrated Water Resource Management Using Water Evaluation and Planning Model: A Case Study of Lower Bari Doab Canal, Pakistan. *Environ. Sci. Proc.* 2023, *4*, x. https://doi.org/10.3390/xxxx

Academic Editor(s):

Published: 15 March 2023



Copyright: © 2023 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/license s/by/4.0/).

The system followed for the distribution of water in agricultural lands of Pakistan. The water is supplied after 7 days according to the turn of each farmer (Hoff et al., 2011). This amount of water supplied to each farmer depends on its land holding i.e., 25 minutes/acre/week. This system is purely supply based and does not consider the water required by the crops grown within an area. This amount of water is distributed throughout the year, but the water demand varies within a year. Sometimes more water is supplied than the crops demand and it gets wasted, and sometimes less water is supplied which is unable to fulfill the demand of the crops grown. This ultimately results in increasing the groundwater pumping to fulfill the demand for crops. So, there is a dire need to develop a system that considers both demand and supply. For the past three decades, many national and international studies were conducted on the water resource management and development, of Pakistan. In these studies water is studied according to different aspects including water security (Ishaque and shaikh, 2017; Mahmood and Liepach, 2012), water balance (Hussain et al., 2011), water and food security (GOP, 2017), Water sector Strategy (Mahmood and liepach, 2012), Food, water and 3 Energy nexus (Rasul and Bikash, 2016) and use different models including Indus Basin Model Revised, to relief water scarcity.

The inadequate political governance and inappropriate policies also cause the mismanagement of the valuable resource of water. Conducting different studies and implementing different projects and policies, requires considerable involvement of various departments and therefore, policy-making in Pakistan is not a facile task. The model used in this study is WEAP. The results obtained from WEAP will help to combat the problems caused by climate change, industrialization, and population growth to water resources and to redesign the water allocation policies by considering both demand and supply. It gives an all-inclusive, adaptable, and easy-to-use structure for planning and policy analysis. WEAP is used for calculating water balance, scenario generation, and policy analysis. It calculates the Water balance based on Crop Water requirements. It also aids in reallocating water resources according to water availability. Different possible future scenarios were built to analyze the water resources. These types of models

Helps, to improve water distribution and to achieve efficient water resource management. This work is thus (1) to investigate the current water allocation scenario in the Lower Bari Doab Canal command area and (2) to evaluate the water allocation plans under different possible future scenarios

2. Material and Method

2.1. Description of Study Area

This study was carried out in the command area of the Lower Bari Doab Canal. This canal originates from Balloki Headworks which lies on the left bank of River Ravi beside Balloki barrage. The gross command area of LBDC is found between 29°53′0″ to 31°13′6″ N latitudes and 71°34′49″ to 73°51′56″ E longitudes. Most of the water reaching the LBDC is from River Jehlum and River Chenab via a link canal. The Gross command area and culturable command area of LBDC are 0.728 M hac and 0.676 M hac, respectively. The length of the main canal is 124 miles, and it irrigates the districts of Kasur, Okara, Sahiwal, and Khanewal. It provides irrigation supplies to 65 nos. of taking channels and 3500 watercourse outlets. Irrigated area for Rabi is 1,579,003.594 acres, and irrigated area for Kharif is 1,448,764.597 acres. The average temperature of the study area is 24.77 °C. Its designed head capacity is 9841 cusecs with a water allowance of 33.3 cusecs/1000 acres. The length of the main canal is 201 km.



Figure 1. Location of Lower Bari Doab Canal Command Area.

2.2. Data Collection

The Water Evaluation and Planning model used in the study is found to be veryeffective for calculating the water demand and the Unmet demand. It is also used for evaluating and analyzing different plans and projects before implementation (Levite et al., 2003). Data required to fulfill the objectives of the study and to obtain the results from the WEAP includes climatic data (maximum temperature, minimum temperature, wind speed, precipitation, cloudiness fraction, Average humidity, wind speed measurement height), crops grown in the area, existing cropping pattern, rotation of crops, the population in the area, domestic demand, soil types data. Data of flow in Lower Bari Doab Canal in all the concerned years. All the mentioned data is collected from various departments. The data along with its sources and format is given in the table below.

Table 1. Data used and its Sources and format for LBDC command area.

Data	Source s	Time
Climatic data	Pakistan Meteorological dept., Monthly and global assembled and satellitedatasets	Daily, Monthly
Flows of LBDC	Irrigation department, GOP	Daily
Land use data	MODIS	Yearly
Soil data	World Soil map.	Daily Discharge data
Population (District wise), Water consumption, Growth rate	Pakistan Bureau of Statistics, WorldBank Data	Yearly record

2.2.1. Soil Data

Soil types within the study area were figured out from the world soil map by using different commands in ArcGIS. These commands include the extraction of the study area soil map from the world soil map which was classified and studied to determine the soil typeswithin the area. The soil map for the study area is shown in the figure below.

Sr. no.	SNUM	Soil Types
1	3736	Clay Loam
2	3878	Loam
3	3883	Clay Loam

Table 2. Soil type and Code.



Figure 2. Soil Map.

2.2.2. Agricultural Land Utilization Data

This data was collected from the classification of the land use data of Pakistan in GIS. Arc Map has been used to superposition this land use with canal command areas. The land use data for both seasons of Rabi and Kharif in each of the districts was extracted from the land use data of Pakistan for both the season of Rabi and Kharif. The extracted land use data was studied excel and changed accordingly to be input in the WEAP. The land use data was input in the CSV format into the WEAP. The data holds information regarding land utilization inall of the four-district laying in the command area of Lower Bari Doab Canal. There two growing seasons are seen in this study area i.e., Rabi and Kharif. The growing season of Rabi is from November to April and the growing season of Kharif is from May to October.



Figure 3. Rabi and Kharif season land use data.

3. Results and Discussion

3.1. Domestic Water Demand of Population within Districts for the Current Account Year (2015)

Domestic water demand includes water requirements for drinking, House chores, and personal cleanliness. The annual water demand of a person is taken as 33.5 m³. The observed population of Kasur, Okara, Sahiwal, and Khanewal in the year 2015 was 792,045, 2,915,324, 2,414,994, and 730,928, respectively. The corresponding domestic water demand for 2015 for Kasur, Okara, Sahiwal, and Khanewal was found to be 31.21 MCM, 101.51 MCM, 80.6 MCM, and 24.45 MCM, respectively. The demand for Okara was seen to be the maximum demand among the districts as the population of Okara was observed to be 2,915,342, which is the maximum among the four districts. The lowest domestic water demand was found to be for the district of Khanewal because of the lowest population among these districts. However, the total domestic water demand within the command areawas seen to be 238.82 MCM for the year 2015.





3.2. Water Demand for Agriculture for the Current Account Year (2015)

Water demand for each of the districts was determined and the water demand of Sahiwal was found to be the most at 1713 MCM as the land cover area in the Sahiwal was almost 742731 Hectares which is the largest land cover of crops among the districts. For ease of understanding the land cover in the southern and northern buffers was also summedup in the Sahiwal. Moreover, the demand priority of Sahiwal was taken as 3 i.e., its demandwill be fulfilled after the demand of Kasur and Okara. Water demand for the district of Kasur was the lowest and calculated as 237.517 MCM as the land use area of crops for Kasur was 17,251 Hectares which is also the lowest land use among districts. The water demand of Okara was 530.3362 followed by the Water demand of Khanewal which was approximated as 445.308 MCM because the land covered by Agriculture for Okara was more than that of Khanewal.





Figure 5. Water demand for Kasur, Okara, Sahiwal and Khanewal.

3.3. Unmet Demand for Kasur, Okara, Sahiwal, and Khanewal for the Current Account Year (2015)

Demand priority of 1,2,3 and 4 was given to the agricultural demand site of Kasur, Okara, Sahiwal, and Khanewal. Demand priority explains the sequence of fulfilling the water demand of the demand sites. The Unmet demand for the district of Kasur and Okara was almost zero because Kasur lies at the start of the LBDC and there is more rainfall within the district of Kasur. Similarly, Okara lies after Kasur and its demand was full before Sahiwal and Khanewal. The Unmet demand for Sahiwal was 567.69 MCM and the Unmet demand for Khanewal was approximated as 344.57 MCM. The unmet demand of Sahiwal was more because its land cover was more than that of Khanewal. This increased cropping pattern results in increased water demand and Unmet demand for the district of Sahiwal.



Figure 6. Unmet demand for Sahiwal and Khanewal.

3.3.1. Low Population Growth Rate

This scenario considers that the population is growing at a lower rate of 1.5% after 2020. Following this growth rate, the water demand will be lower for all of the considered years as compared to the higher population growth rate. For Kasur, water demand is 31.20 MCM in 2015, 34.53 MCM in 2020, 37.20 MCM in 2025, 40.044 MCM in 2030, and 46.511 in 2030. For Khanewal the domestic water demand was estimated to be 25.449 MCM in 2015, 28.163 MCM in 2020, 32.684 MCM in 2030, and 37.931 MCM in 2040. The highest water demand was observed in Okara for all of the year's upto 2040 as compared to all other districts. Okara's water demand rise to 151.291 MCM in 2040. Sahiwal water demand was observed to be 89.26 MCM in 2020 and 120.22 MCM in 2040.



Lower Population Growth Rate

Figure 7. Low population growth.

3.3.2. Medium Population Growth Rate

The scenario of a medium population growth rate took a 2.03% growth rate per year. Following this growth rate, the water demand in Kasur was observed as 31.206 MCM in 2015, 34.53 MCM in 2020, 42.22 MCM in 2030, and 51.61 MCM in 2040. Water demand increases from 25.44 MCM in 2015 to 42.095 MCM in 2040. Water demand forSahiwal was observed as 80.66 MCM in 2015, 89.260 in 2020, 109.128 in 2030, and 133.418 in 2040. Highest water demand was observed to be for the district of Okara for allof the years at 101.507 MCM in 2015, increased to 112.32 MCM in 2020, 137.33 MCM in2030, and highest in 2040 167.9 MCM. Similarly, (Hassan et al., 2019) took a growth rate for 2.41% for Sindh and 2.13% for Punjab the water demand will aggravate from 177.8 BCM in 2017 to 192.7 BCM in 2040.



Medium Population Growth Rate

Figure 8. Medium Population Growth rate.

3.3.3. High Population Growth Rate

This scenario assumes that the high population growth alone results in more development and economic growth. The agricultural land is decreasing as there is more urbanization. Fields are being reduced day by day to make new settlements for a growing population. Economic growth results increase in water demand for a person in the year. This scenario considers the increase in water demand to 55 m³/year. This increase in water use results in a rapid increase in water demand up to the year 2040. In the Higher population growth rate scenario domestic water demand increased to 56.581 MCM, 46.148 MCM, 184.0645 MCM, and 146.263 MCM in Kasur, Okara Sahiwal, and Khanewal, respectively in 2040. But this scenario considers the increase in the annual water use rate per person to 55 m³/year and the higher population growth rate i.e., 2.5%/year. Domestic Water demand for Kasur district increased from 31.026 MCM in 2015 to 93.183 MCM in 20140 following the higher population growth rate and increase in annual water use by a person. For the district of Khanewal the domestic water demand changed from 25.449 MCM to 54.808 in 2020, 62.01 MCM in 2025, 70.15 in 2030, 79.379 in 2035, and 89.810 in 2040.



Figure 9. High Population growth rate.

3.4. Higher Living Standard Scenario

The highest domestic water demand was observed to be for the district of Okara the water demand was recorded as 101.507 MCM in 2015, 218.606 in 2020, 279.83 in 2030, and 358.21 MCM in 2040. For the district of Sahiwal, the water demand was estimated to be 80.66 MCM in 2015 which increased to 284.645 MCM in 2040. (Amin et al., 2018) also used WEAP to access the impact of higher population growth rate and urbanization on water demand in the Upper Indus Basin. The water demand increased in both situations. He also concluded that an increase in population and more urbanization results in an increase in water demand and ultimately higher unmet demand. The higher unmet demand will lead to an increase in groundwater abstraction which causes the rapid deterioration of groundwater quantity and quality.





Figure 10. High Living Standards.

4. Conclusions & Recommendations

Water demand is increasing with increasing population, economic growth, urbanization, Industrialization, and Climate change. Water demand for the Sahiwal district was found to be maximum because it has the largest land use area for crops. Unmet demand was found to be the highest for the districts of Sahiwal and Khanewal. WEAP is userfriendly and can be used easily for the evaluation of different water management strategies and policies before implementation. The constraints faced include the unavailability of institutional support, sufficient and reliable information, and political conflicts. To meet the unmet demand, protect the groundwater resource from deterioration, and mitigate the effects of climate change the water should be supplied on a demand basis rather than a supply basis. The wastewater can be treated and then can be used for irrigation purposes. This can help to reduce the irrigation demand, changing the cropping pattern and the use water efficient crops in the district of Sahiwal and Khanewal can reduce the water demand in these areas. Efficient irrigation methods such as sprinklers and drip irrigation can also help in reducing water demand. The domestic demand can be reduced bays maintaining a low population growth rate and using water-efficient taps in the houses. Consumer education and awareness level would affect his water use and practices, which could result in water demand reduction. WEAP is user-friendly and can be used for figuring out the impact of different water management strategies and policies.

Acknowledgments: This research was supported by a Research project of Pakistan Science Foundation No. PSF/CRP/18th Protocol (10). Agricultural Remote Sensing Lab, University of Agriculture Faisalabad

References

- 1. Amin, A.; Iqbal, J.; Asghar, A.; Ribbe, L. Analysis of current and future water demands in the Upper Indus Basin under IPCC climate and socio-economic scenarios using a hydro-economic WEAP Model. *Water* **2018**, *10*, 537.
- 2. Anonymous. Global Risks Report 2019; World Economic Forum: Geneva, Switzerland, 2019; p. 114.
- 3. GoP. Pakistan Vision 2025: One Nationa One Vision; Ministry of Planning Development and Reform: Islamabad, Pakistan, 2017.
- Hassan, D.; Rais, M.; Ahmed, W.; Bano, R.; Burian, S.; Ijaz, M.; Bhatti, F. Future water demand modeling using water evaluation and planning: A case study of the Indus Basin in Pakistan. *Sustain. Water Resour. Manag.* 2019, *5*, 1903–1915. https://doi.org/10.1007/s40899-019-00343-0.
- 5. Hoff, H.; Bonzi, C.; Joyce, B.; Tielbörger, K. A water resources planning tool for the Jordan River basin. *Water* **2011**, *3*, 718–736.
- 6. Hussain, I.; Hussain, Z.; Sial, M.; Akram, W.; Farhan, M. Water Balance, Supply and Demand and Irrigation Efficiency of Indus Basin. *Water* **2011**, *49*, 13–38.
- 7. Ishaque, W.; Shaikh, S. Water and Energy Security for Pakistan; A retrospective analysis. *Grassroots* 2017, 51, 1–14.
- 8. Levite, H.; Sally, H.; Cour, J. Testing water demand management scenarios in a water-stressed basin in South Africa: Application of the WEAP model. *Phys. Chem. Earth* **2003**, *28*, 779–786.
- 9. Mahmood, Z.; Liepach, W. A Productive and Water-Secure Pakistan: Infrastructure, Institutions, Strategy, the Report of the Water Sector Task Force of the Friends of Democratic Pakistan; Water Sector Task Force: Islamabad, Pakistan, 2012.
- 10. Oki, T.; Kanae, S. Global hydrological cycles and world water resources. *Science* 2006, 313, 1068–1072.
- 11. Rasul, G.; Sharma, B. The nexus approach to water–energy–food security: An option for adaptation to climate change. *Clim. Policy* **2016**, *16*, 682–702.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.