

**ASEC  
2022**

**The 3rd International Electronic  
Conference on Applied Sciences**

**01-15 DECEMBER 2022 | ONLINE**

# **A Review on Recent Developments in Passive Plasma Separators Lab-on-Chip Microfluidics Devices**

 *applied sciences*



**Presented By  
Shamima Khatoon  
Ph.D Scholar**

Department of Electrical Engineering  
Faculty of Engineering  
**Dayalbagh Educational Institute (Deemed to be University)**


**01<sup>st</sup> December 2022**

# Presentation Outlines

- ☐ Lab-On-Chip Devices
- ☐ Significance of Plasma Separation
- ☐ Microfluidics and Bioseparation
- ☐ Blood Component and Plasma Separation
- ☐ Literature Survey on the existing Plasma Separators
- ☐ References


# Lab-On-Chip Devices

- ❑ Lab-On-Chip Devices (LOC) are also called as ( $\mu$ -TAS) or are the miniaturized measurement devices.
- ❑ These systems aims to integrate several steps into a single, **automated device** or 'chip'.
  1. Sample Collection
  2. Sample Preparation
  - 3. Biomixing and Bioseparation**
  4. Sample Transfer for Analysis
  5. Detection and Results
- ❑ The LOC systems usually consist of two units
- ✓ A set of **microfabricated chambers and channels**,



# Significance of Qualitative Rapid Biosensing

- ❑ Compatible to **Resource limited rural areas.**
- ❑ Preferred for **Rampant disease management.**
- ❑ **Mass detection and disease control** in Pandemic Situations like COVID-19.
- ❑ **Early detection and control at the very first acute stage of infection.**
- ❑ **POCT and faster health recovery**




# Need of Plasma Separation

---

- ❑ Plasma contains all necessary **Proteins, RNAs, DNAs, Enzymes** facilitates testing through Biosensing Card Testing Platform
- ❑ Both **turn around time and accuracy** of diagnosis results are improved after RBCs and WBCs removal.
- ❑ **Plasma Testing** forms the bases of Biosensing Cards with **Greater Reliability**
- ❑ Plasma Samples are much **easier in handling and storage** as compared to whole blood sample
- ❑ Plasma itself rich in **anticoagulant Anti-Thrombin-III**, so it cannot be easily coagulated.

# Microfluidics and Bioseparation

- ❑ Microfluidics is the scientific/engineering discipline underlying  $\mu$ -TAS
- ❑ **Process or manipulate** small amounts of fluidics, i.e. 2-5ml, using channels measuring from tens to hundreds of micrometers.







# Blood Components and Plasma Separation Techniques

❑ **Active separation** methods exploit external forces and makes use of electrical, magnetic, dielectrophoretic, acoustics properties of blood cells.


❑ **Passive separation** methods employ internal rheology of blood components and simply use differences in cell properties for self-separation, such as the size, weight, shape, or stiffness.



# Active Plasma Separation

❑ Centrifuge-Tube Based (Fig. A)

❑ CD-based (Fig.B)



As described by Stokes' Law, the sedimentation rate of a particle,  $v_r$ , due to centrifugal force is:

$$v_r = \frac{dr}{dt} = \frac{(\rho_p - \rho_m(r)) \cdot d^2 \cdot r \cdot \omega^2}{18 \cdot \eta_m(r)}$$

and

$$rpm = \sqrt{\frac{RCF}{2.839 \times 10^{-5} \cdot r}}$$

Where,

$\rho_p$  is the particle density,

$\rho_m(r)$  is the media density at a given  $r$ ,

$d$  is the diameter of the particle,

$r$  is the radial distance from the rotation center,

$\omega$  is the angular velocity,  $\eta_m(r)$  is the media viscosity at a given radius


and **RCF** is relative centrifugal force.



# Passive Plasma Separation


## ❑ Microfluidics-based (Fig.A)

Plasma follows *bifurcations* through Cell-Free Region due to Newtonian Behaviour.



## ❑ Microfilters-based (Fig. B)

Microfilters are also preferred for *size selection trapping* and extraction of target particles.



# Literature Survey on Plasma Separators

## 1. Active Devices based on Centrifugation

- ❑ Amasia and Madau et.al in **2010**, fabricated a **multilayer compact-disc centrifugal microfluidic device** using traditional **plastics machining techniques**.
- ❑ Moore et al. in **2011**, fabricated capillary valves in the centrifugal microfluidic disc by designing patterned surfaces, emphasizing on the **3D Printing Techniques**.








Fig. Device Structure and Spin profile graph detailing rotational velocity over time during the on-disc plasma separation process.

## 2. Passive Devices (Miniaturized On-Chip Separators) fabricated using various techniques

### 2.1. PDMS Soft Lithography

- ❑ Sara et.al (2006)- Separation Membrane-assisted Microfiltration and capillary force driven plasma extraction of high purity in lesser time (Fig. A)
- ❑ Park et.al (2015) – Retarded flow-assisted sedimentation, microfiltration and free-flow wetting of ethanol-treated collection channel (Fig. B)
- ❑ Madadi et.al (2015) - Separation Science, Fluid Dynamics, and Blood Rheology (Fig. C)




## 2. Passive Devices.....contd.

### 2.2. Devices Fabricated Using Hybrid Technologies

Integration of Hybrid Chips fabricated using Standard Photolithography and PDMS Soft-Lithography

- ❑ Sollier et.al (2009) - Innovative device is based on the lateral migration of red cells and the resulting cell-free layer, which is used to supply geometric singularities (an ear-cavity or a corner-edge) and locally enhanced clear plasma region (Fig. A)






DLP 3D Printing, SU-8 Photolithography followed with PDMS Soft Lithography.

- ❑ Maria et.al (2016) - Capillary flow of blood in a microchannel with differential wetting, to induce a self- built-in filter for plasma separation and subsequent chromatographic detection of glucose (Fig. B)

## 2. Passive Devices.....contd.

### 2.3. CNC Micromachining

- ❑ Su et. al (2020), modular universal plasma-separation microdevice based on immunocapture and size filtering (Fig. A).



### 2.4. DLP 3D Printing

- ❑ Liu et. al (2015) introduces membrane based superhydrophobic clamshell style Plasma Separator. Gravitation assisted sedimentation and membrane-based filtration, while Superhydrophobic Surface-assisted Size extraction of plasma (Fig. B).

### 2.5. SLA 3D Printing

- ❑ Kim et. al (2022) – Glass fibre filter based erythrocyte binding, self-pressure driven plasma separation and multiple LFA diagnosis (Fig. C).

# Acknowledgement

---

I am thankful to the Ministry of Science & Technology, **DST-WISE- KIRAN Division** for funding the research proposal.



# REFERENCES

1. Civelekoglu, O.; Frazier, A.B.; Sarioglu, A.F. The Origins and the Current Applications of Microfluidics-Based Magnetic Cell Separation Technologies. *Magnetochemistry* **2022**, *8*, 10. <https://doi.org/10.3390/magnetochemistry8010010>
2. Garcia-Rey, S.; Nielsen, J.B.; Nordin, G.P.; Woolley, A.T.; Basabe-Desmonts, L.; Benito-Lopez, F. High-Resolution 3D Printing Fabrication of a Microfluidic Platform for Blood Plasma Separation. *Polymers* **2022**, *14*, 2537. <https://doi.org/10.3390/polym14132537>
3. Lopresti, F.; Keraite, I.; Ongaro, A.E.; Howarth, N.M.; La Carrubba, V.; Kersaudy-Kerhoas, M. Engineered Membranes for Residual Cell Trapping on Microfluidic Blood Plasma Separation Systems: A Comparison between Porous and Nanofibrous Membranes. *Membranes* **2021**, *11*, 680. <https://doi.org/10.3390/membranes11090680>
4. Hanbi Kim, Hyeonseek Park, Doo Ryeon Chung, Taekyung Kim, Eunkyong Park, Minhee Kang, A self-pressure-driven blood plasma-separation device for point-of-care diagnostics. (2022) *Talanta*, 247, 123562. <https://doi.org/10.1016/j.talanta.2022.123562>
5. Nair, K.P.P.R.; Veettil, T.C.P.; Wood, B.R.; Paul, D.; Alan, T. Haemoprocessor: A Portable Platform Using Rapid Acoustically Driven Plasma Separation Validated by Infrared Spectroscopy for Point-of-Care Diagnostics. *Biosensors* **2022**, *12*, 119. <https://doi.org/10.3390/bios12020119>
6. Eke, C. S., Jammeh, E., Li, X., Carroll, C., Pearson, S., & Ifeachor, E. (2021). Early Detection of Alzheimer's Disease with Blood Plasma Proteins Using Support Vector Machines. *IEEE journal of biomedical and health informatics*, 25(1), 218–226. <https://doi.org/10.1109/JBHI.2020.2984355>
7. Wang, Y.; Nunna, B.B.; Talukder, N.; Etienne, E.E.; Lee, E.S. Blood Plasma Self-Separation Technologies during the Self-Driven Flow in Microfluidic Platforms. *Bioengineering* **2021**, *8*, 94. <https://doi.org/10.3390/bioengineering80700>
8. Su, X., Zhang, J., Zhang, D., Wang, Y., Chen, M., Weng, Z., Wang, J., Zeng, J., Zhang, Y., Zhang, S., Ge, S., Zhang, J., & Xia, N. (2020). High-Efficiency Plasma Separator Based on Immunocapture and Filtration. *Micromachines*, 11(4), 352. <https://doi.org/10.3390/mi11040352>
9. Jørgensen, M. K., Eriksen, K. B., & Christensen, M. L. (2020). Particle Track and Trace during Membrane Filtration by Direct Observation with a High Speed Camera. *Membranes*, 10(4), 68. <https://doi.org/10.3390/membranes10040068>
10. Yasukawa, T.; Yamada, J.; et.al. Microfluidic Separation of Blood Cells Based on the Negative Dielectrophoresis Operated by Three Dimensional Microband Electrodes. *Micromachines* **2020**, *11*, 833. <https://doi.org/10.3390/mi11090833>
11. Mateen, S.A., Bhole, K.S. A review on microfluidic devices for separation of blood constituents. *ICEMEM-2019. IOP Conf. Series: Materials Science and Engineering* 810 (2020) 012024. <http://dx.doi.org/10.1088/1757-899X/810/1/012024>
12. Wang, Y., Keller, K., & Cheng, X. (2019). Tangential Flow Microfiltration for Viral Separation and Concentration. *Micromachines*, 10(5), 320. <https://doi.org/10.3390/mi10050320>
13. Wei Chien, Zunmin Zhang, Gerhard Gompper, and Dmitry A. Fedosov, "Deformation and dynamics of erythrocytes govern their traversal through microfluidic devices with a deterministic lateral displacement architecture", *Biomicrofluidics* 13, 044106 (2019) <https://doi.org/10.1063/1.5112033>
14. Rhee MK, Ho Y-L, Raghavan S, Vassy JL, Cho K, Gagnon D, et al. (2019) Random plasma glucose predicts the diagnosis of diabetes. *PLoS ONE* 14(7): e0219964. <https://doi.org/10.1371/journal.pone.0219964>
15. Benjamin, R. J., & McLaughlin, L. S. (2012). Plasma components: properties, differences, and uses. *Transfusion*, 52 Suppl 1, 9S–19S. <https://doi.org/10.1111/j.1537-2995.2012.03622.x>
16. Nader, E. Blood Rheology: Key Parameters, Impact on Blood Flow, Role in Sickle Cell Disease and Effects of Exercise. *Front. Physiol.*, 17 October **2019**. Sec. Red Blood Cell Physiology. <https://doi.org/10.3389/fphys.2019.01329>
17. Raiza, N. Kazi. Early detection of kidney function in diabetic kidney disease: An approach to prevent end stage renal disease *Journal of Interventional Nephrology* (2018) 1(1), 15–18
18. Faustino, V.; Catarino, S.O.; Pinho, D.; Lima, R.A.; Minas, G. A Passive Microfluidic Device Based on Crossflow Filtration for Cell Separation Measurements: A Spectrophotometric Characterization. *Biosensors* **2018**, *8*, 125. <https://doi.org/10.3390/bios8040125>

# REFERENCES...contd.

19. Rafeie, M., Zhang, J., Asadnia, M., Lib, W., and Warkiani, M. E. Multiplexing slanted spiral microchannels for ultra-fast blood plasma separation. **(2016)** Lab on a Chip, 16(15), 2791–2802. <https://doi.org/10.1039/C6LC00713A>
20. Maria, M. S., Rakesh, P. E., Chandra, T. S., & Sen, A. K. **(2016)**. Capillary flow of blood in a microchannel with differential wetting for blood plasma separation and on-chip glucose detection. *Biomicrofluidics*, 10(5), 054108. <https://doi.org/10.1063/1.4962874>
21. Namgung, B.; Tan, J.K.S.; Wong, P.A.; Park, S.-Y.; Leo, H.L.; Kim, S. Biomimetic Precapillary Flow Patterns for Enhancing Blood Plasma Separation: A Preliminary Study. *Sensors* **2016**, 16, 1543. <https://doi.org/10.3390/s16091543>
22. Park, S., Shabani, R., Schumacher, M. *et al.* On-chip whole blood plasma separator based on microfiltration, sedimentation and wetting contrast. *Microsyst Technol* **22**, 2077–2085 **(2016)**. <https://doi.org/10.1007/s00542-015-2656-7>
23. Madadi, H., Casals-Terré, J., & Mohammadi, M. **(2015)**. Self-driven filter-based blood plasma separator microfluidic chip for point-of-care testing. *Biofabrication*, 7(2), 025007. <https://doi.org/10.1088/1758-5090/7/2/025007>
24. Schwarzenbach, H., Hoon, D. S., & Pantel, K. **(2011)**. Cell-free nucleic acids as biomarkers in cancer patients. *Nature reviews. Cancer*, 11(6), 426–437. <https://doi.org/10.1038/nrc3066>
25. Moore, J.L., McCuiston, A., Mittendorf, I. *et al.* Behavior of capillary valves in centrifugal microfluidic devices prepared by three-dimensional printing. *Microfluid Nanofluid* 10, 877–888 **(2011)**. <https://doi.org/10.1007/s10404-010-0721-1>
26. Wagner, J. **(2012)**. Free DNA—new potential analyte in clinical laboratory diagnostics?. *Biochemia medica*, 22(1), 24–38. <https://doi.org/10.11613/bm.2012.004>
27. Zhang, X. B., Wu, Z. Q., Wang, K., Zhu, J., Xu, J. J., Xia, X. H., & Chen, H. Y. **(2012)**. Gravitational sedimentation induced blood delamination for continuous plasma separation on a microfluidics chip. *Analytical chemistry*, 84(8), 3780–3786. <https://doi.org/10.1021/ac3003616>
28. Franklin, B. S., Vitorino, B. L., *et al.* **(2011)**. Plasma circulating nucleic acids levels increase according to the morbidity of Plasmodium vivax malaria. *PloS one*, 6(5), e19842. <https://doi.org/10.1371/journal.pone.0019842>
29. Amasia, M., Madau, M. Large-volume centrifugal microfluidic device for blood plasma separation. October **2010** *Bioanalysis* 2(10):1701-10. <https://doi.org/10.4155/bio.10.140>
30. Rodriguez-Villarreal A I, Arundell M, Carmona M and Samitier J High flow rate microfluidic device for blood plasma separation using a range of temperatures, **2010**. Lab Chip 10 211-19. <https://doi.org/10.1039/B904531G>
31. Zheng, S.; Lin, H.; Liu, J.-Q.; Balic, M.; Datar, R.; Cote, R.J.; Tai, Y.-C. Membrane microfilter device for selective capture, electrolysis and genomic analysis of human circulating tumor cells. *J. Chromatogr. A* **2007**, 1162, 154–161
32. Rainer, T. H., Wong, L. K., Lam, W., Yuen, E., Lam, N. Y., Metreweli, C., & Lo, Y. M. **(2003)**. Prognostic use of circulating plasma nucleic acid concentrations in patients with acute stroke. *Clinical chemistry*, 49(4), 562–569. <https://doi.org/10.1373/49.4.562>
33. Moorthy and D.J. Beebe, In situ fabricated porous filters for microsystems. Lab Chip 3, 62 **(2003)**. <https://doi.org/10.1039/B300450C>
34. H. Andersson, W. van der Wijngaart, P. Enoksson, and G. Stemme, Micromachined flow-through filter-chamber for chemical reactions on beads. *Sensors and Actuators B-Chemical* 67, 203 **(2000)**.
35. Kalmokoff, M.L., Koval, S.F. & Jarrell, K.F. Relatedness of the flagellins from methanogens. *Arch. Microbiol.* **157**, 481–487 **(1992)**. <https://doi.org/10.1007/BF00276766>
36. Cripps, CM. Rapid method for the estimation of plasma haemoglobin levels. *Journal of Clinical Pathology* **1968**; 21:110-112.

**THANK YOU!!**