The 5th International Online Conference on Nanomaterials



22-24 September 2025 | Online

THE MOST PRACTICAL, ECONOMICAL SOLUTION to overcome environmental disasters, fires, and frost cycles with the most sustainable, durable, and green concrete


Mr. *Ibrahim Monir Kandil* – Civil Eng. Consultant – Alex University Egypt Sciforum: 122729 +201227944661 – info@kandiel.net



INTRODUCTION & AIM

Our goal:

We aim to reach concrete structures (low to medium rise) resist harmful environmental factors:



All these are achieved by using

lightweight structural comcrete called: KANDCRETE

METHOD: USING High Performance Concrete

Raw Materials

Normal weight Aggregate (natural sand – natural gravel)

Cement, preference Ordinary Portland Cement (OPC) or (SRC) 350-400 kg/m3

Water for concrete Mixture

Foaming Agent

Silica Fume min. 5% of cement content

Fiber: fiber glass

Admixtures

Density

1650 kg/m3 to **1850** kg/m3

Compressive strength


Table 1 : Compressive Strength Of Cube Concrete (KandCrete)

Specimens at different ages


Sample	Dimension	Strength @ 28 days Kg/cm2	Strength @ 45 days Kg/cm2	Strength @ 240 days Kg/cm2	strength @ 570 days Kg/cm2
R	Cube 150x150x150	368	443	525	665
S	Cube 150x150x150	303	377	425	585

RESULTS & DISCUSSION


Compressive strength charts




Water Permeability Test Results:



Heat Transfer Test Results charts



Fire Resistance Test Results charts



CONCLUSION and RECOMMENDATION

(KandCrete)

Considered as an innovative product for the human civilization, for the days to come & is expected to show its multi-various facets in all the spheres of construction yet to be explored in the hands of future researchers.