

Abstract

Eucalyptus Biochar as a Sustainable Nanomaterial for Electrochemical Sensors [†]

Annalisa Scroccarello ^{1,*}, Flavio Della Pelle ¹, Qurat Ul Ain Bukhari ¹, Filippo Silveri ¹, Daniele Zappi ², Enrico Cozzoni ³ and Dario Compagnone ¹

¹ Faculty of Bioscience and Technology for Food, Agriculture and Environment University of Teramo, Via Renato Balzarini 1, 64100, Teramo, Italy; fdellapelle@unite.it (F.D.P.); dcompagnone@unite.it (D.C.)

² Biosensor, Via Olmetti 44, 00060, Formello, Roma, Italy; daniele.zappi@uniroma1.it

³ GRADO ZERO INNOVATION, Via nove 2/A, 50056, Montelupo F.no, Firenze, Italy

* Correspondence: ascroccarello@unite.it

[†] Presented at the 1st International Electronic Conference on Chemical Sensors and Analytical Chemistry, 01–15 July 2021; Available online: <https://csac2021.sciforum.net/>.

Abstract: Carbonaceous-based nanomaterials (C-NMs) are the pillar of myriad sensing and catalytic electrochemical applications. In this field, the search for environmentally sustainable C-NMs from renewable sources became a duty in the development of nano-sensors. Herein, water-soluble carbon nanofibers (CF) were produced from eucalyptus scraps-based biochar (BH) through an ultrasound treatment, assisted by sodium cholate used as a stabilizing agent. The BH-CF was investigated as sensing material onto commercial screen-printed electrodes via drop-casting (BH-SPE) and as thin-film fully integrated into a lab-made flexible electrode. The thin film was produced via BH-CF vacuum filtration followed by the film transferring to a thermo-adhesive plastic substrate through thermal lamination. This approach gave rise to a conductive BH-CF film (BH-Film) easily embodied in a lab-made electrode produced with office-grade instrumentation (i.e., craft-cutter machine, thermal laminator) and materials (i.e., laminating pouches, stencil). The BH-CF amount was optimized and the resulting film morphologically characterized, then, the electrochemical performances were studied. The BH-CF electrochemical features were investigated towards a broad range of analytes containing phenol moieties, discrimination between ortho- and mono-phenolic structures were achieved for all the studied compounds. As proof of applicability, the BH-CF-based sensors were challenged for simultaneous determination of mono-phenols and ortho-diphenols in olive oil extracts. LODs $\leq 0.5 \mu\text{M}$ and $\leq 3.8 \mu\text{M}$ were obtained for hydroxytyrosol (o-diphenol reference standard) and Tyrosol (m-phenols reference standard), respectively. Moreover, a high inter-sensors precision (RSD calibration-slopes $\leq 7 \%$, $n = 3$) and quantitative recoveries in sample analysis (recoveries 91–111%, RSD $\leq 6 \%$) were obtained. Here, a solvent-free strategy to obtain water-soluble BH-CF was proposed, and their usability to sensor fabrication and modification proved. This work demonstrated as cost-effective and sustainable renewable sources, rationally used, can lead to obtain useful nanomaterials.

Keywords: Biochar; sensor; nanomaterial

Published: 6 July 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).